


gasket material		permissible operating temperature TS
XX	spezifikation	
VI	FPM / FKM	-20°C...+80°C
NBR	NBR	-10°C...+80°C
GF	FPM GF / FKM GF	-20°C...+80°C
EP	EPDM	-40°C...+80°C
TH	HNBR (Therban)	-20°C...+80°C
CH	Chemraz 505	-30°C...+80°C
CT	Chemraz 564 LT	-40°C...+80°C
KA	Kalrez 6375	-20°C...+80°C

		ENTGRATEN UND SCHARFE KANTEN BRECHEN		ZEICHNUNG NICHT SKALIEREN		ÄNDERUNG	
				WERKSTOFF: Stainless Steel			
		DATUM		NAME		BENENNUNG:	
		01.04.2016		Petri		DryCon® - Coupler (Hose Unit) DN50 (2") - KD70 Connection: Flange EN1092-1B DN50 PN25	
		GEZEICHNET		GEPRÜFT		ZEICHNUNGSNR.	
				GENEHMIGT		9DCM-050-VAXX-F25	
				 Schlauch- und ArmaturenService		A3	
Zust		Änderung		Datum		Name	
				GEWICHT: 6,8kg		MASSSTAB:1:1	
						BLATT 1 VON 1	