



wrench size 100mm

gasket material		permissible operating temperature TS
XX	spezifikation	
VI	FPM / FKM	-20°C...+80°C
NBR	NBR	-10°C...+80°C
GF	FPM GF / FKM GF	-20°C...+80°C
EP	EPDM	-40°C...+80°C
TH	HNBR (Therban)	-20°C...+80°C
CH	Chemraz 505	-30°C...+80°C
CT	Chemraz 564 LT	-40°C...+80°C
KA	Kalrez 6375	-20°C...+80°C

		ENTGRATEN UND SCHARFE KANTEN BRECHEN		ZEICHNUNG NICHT SKALIEREN		ÄNDERUNG	
				WERKSTOFF: Stainless Steel			
		DATUM		NAME		BENENNUNG: DryCon® - Adaptor (Tank Unit)	
		04.04.2016		Petri		DN80 (3") - KD119	
		GEPRÜFT				Connection: G3 (3") ISO 228-1 (BSPP)	
		GENEHMIGT				ZEICHNUNGSNR. 9DCV-080-VAXX	
				FlexoTech GmbH Schlauch- und ArmaturenService		A3	
Zust	Änderung	Datum	Name	GEWICHT: 3,7kg		MASSSTAB:1:1	
						BLATT 1 VON 1	